## IN THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) A method for passively monitoring the servicing of a work vehicle during

distribution of fluid products from a service vehicle to one or more fill ports of the work vehicle, [each said fill port having an identifying data source associated therewith for identifying at least the fill port and the type of fluid product appropriate for input\_thereto,] comprising the steps of:

- (a) providing a plurality of magnetically encoded port identifying data sources;
- (b) attaching one of said data sources to each fill port on a vehicle to be serviced, each said data source being encoded to contain port data relating to the identity of the vehicle, the identity of the fill port, and the type of fluid product to be dispensed to the fill port;
- (c) making [ready] one of a plurality of [the] means for distribution of [a] particular types of fluid products ready for dispensation from a service vehicle;
- (d) determining at the service vehicle the type of fluid product being made ready for distribution;
- (e) obtaining at the work vehicle a first set of <u>port</u> data from a data\_source associated with a particular vehicle <u>fill</u> port [to be serviced] selected for service, and transmitting said first set of data to the service vehicle;
- (f) receiving at the service vehicle the transmitted first set of <u>fill port</u> data and using same together with the known type of fluid product <u>made</u> ready for distribution to determine whether or not the selected <u>fill</u> port is about to be serviced with an appropriate fluid product, and generating a signal commensurate therewith;
  - (g) distributing the fluid product to the selected fill port;
- (h) obtaining at the service\_vehicle a second set of data associated with the distribution of the particular type of fluid product to the selected <u>fill</u> port; and
  - (i) logging the signal, the received first set of data and the second set of data.
- 2. (Currently amended) A method for passively monitoring the servicing of a vehicle during distribution of fluid products thereto as recited in claim 1, wherein steps (a)



through (i) are repeated until service of each fill port on the vehicle is complete.

- 3. (Currently amended) A method for passively monitoring the servicing of a vehicle during distribution of fluid products thereto as recited in claim 1, [wherein] and further comprising: causing a horn [is] to be actuated by [the] said signal to validate selection of [the] each port as the intended port to be filled.
- 4. (Currently amended) A method for passively monitoring the servicing of a vehicle during distribution of fluid products thereto as recited in claim 1, [wherein] and further comprising: causing [the] said signal [causes the sounding of] to sound an alarm [, the alarm] warning of any improper distribution of the product.

## 5 - 8 (Canceled)

- 9. (Currently amended) A system for passively monitoring [the servicing of a vehicle during] distribution of fluid products from a mobile service vehicle to fill ports on a vehicle to be serviced, comprising:
- (a) magnetically encoded and readable indicia means affixed to a vehicle to be serviced and positioned proximate to each fill port thereof, each said indicia means providing a first set of data uniquely associated with a particular fill port to be serviced;
- (b) magnetically responsive reader means for reading said indicia means and for transmitting the first set [to] of data to the service vehicle;
  - (c) means on said service vehicle for receiving the transmitted first set of data;
- (d) logic <u>on said service vehicle for determining</u> [ that determines] whether or not said first set of data identifies a particular <u>fill</u> port intended to be serviced and [that generates] <u>for generating</u> a signal commensurate therewith;
- (e) apparatus for generating a second set of data associated with [the distribution of] a fluid product <u>made ready for distribution</u> to the selected fill port; and
- (f) logic [that logs] for logging the signal, the first set of data and the second set of data.

## 10. (Canceled)



selection of the port as the intended port to be serviced.

- 12. (Currently amended) A system for passively monitoring [the servicing of a vehicle during] distribution of fluid products from a mobile service vehicle to fill ports on a vehicle to be serviced, as recited in claim 9, wherein [the] signal [causes the sounding of] is used to sound an alarm warning of any improper distribution of the product.
- 13. (Currently amended) A system and apparatus for passively monitoring distribution of fluid products from distribution sources to fill ports on a vehicle, comprising:

a <u>magnetically</u> encoded port identifying means associated with each fill port on a vehicle to be serviced, said port identifying means containing port data relating to the identity of the vehicle, the identity of the fill port, and the type of material to be dispensed to the fill port;

magnetic reader means for reading said port data and transmitting same to a remote receiver associated with the distribution sources of said fluid products;

flow monitoring means associated with said remote receiver and the distribution sources and operative to generate flow data indicating a particular distribution source, the type of fluid to be dispensed from said particular <u>distribution</u> source, and the volume of fluid actually dispensed from said particular <u>distribution</u> source <u>in servicing a fill port</u>;

means associated with said flow monitoring means\_for comparing said port data to said flow data and operative to generate an alarm in the event that any aspect of said port data is incompatible with any aspect of said flow data; and

means for producing a record of said port data, said flow data and the fact that an alarm was generated.

14. (Currently amended) An apparatus as recited in claim 13, wherein said port data includes information relating to the type of material to be distributed to a particular type of <u>fill</u> port.



- 15. (Currently amended) An apparatus as recited in claim 13, wherein the flow monitoring means includes a lookup table identifying the type of material to be put into a particular type of <u>fill</u> port.
- 16. (Currently amended) An apparatus as recited in claim 13, and further comprising means for determining the location of said vehicle to be serviced and the time of servicing, and for reporting same to said means for producing a record, whereby such location and time of servicing is included in said record.
- 17. (Currently amended) An apparatus as recited in claim 13, wherein said port identifying means includes an array of indicators organized so that when inspected, a set of code terms can be developed uniquely identifying a particular vehicle, a particular port and the type of material to be distributed to said particular <u>fill</u> port.
- 18. (Currently amended) An apparatus as recited in claim 13, wherein said reader means is further operative to generate operator data identifying the operator responsible for servicing said vehicle, and to transmit said operator data to said remote receiver.
- 19. (Currently amended) An apparatus as recited in claim 14, wherein said port identifying means includes an array of <u>magnetic</u> indicators <u>respectively polarized and</u> organized so that when inspected, a set of code terms [can be] <u>are</u> developed uniquely identifying said vehicle, the associated port and the type of material to be distributed to said associated port.
- 20. (Currently amended) An apparatus as recited in claim 14, wherein said <u>magnetic</u> reader means is further operative to generate operator data identifying the operator responsible for servicing said vehicle and for transmitting said operator data to said remote receiver.
- 21. (Currently amended) An apparatus as recited in claim 15, wherein said <u>magnetic</u> reader means is further operative to generate operator data identifying the operator responsible for servicing said vehicle and for transmitting said operator data to said remote receiver.
- 22. (Currently amended) A method of passively monitoring the servicing of a vehicle during distribution of fluid products to fill ports on the vehicle, comprising the steps of:



using an array of polarized magnets to uniquely identify[ing particular] each fill port[s] on a vehicle to be serviced [by providing identifying means], each said array being positioned proximate [each] one of said fill ports and containing port data relating to the identity of the vehicle and the identity of the corresponding port;

using a magnetic reader to read [reading said] the port data associated with a particular port and to transmit[ting same] the port data to a remote receiver;

monitoring the source of fluid product as it is distributed to a particular <u>fill</u> port and generating flow data [indicating] <u>identifying</u> the source, the type of fluid product to be dispensed from <u>the</u> source, and the volume of fluid product actually dispensed from the source <u>to the particular fill port</u>;

comparing said port data to said flow data and generating an alarm in the event that any aspect of said port data is incompatible with any aspect of said flow data; and

producing a record of said port data, said flow data and the fact that an alarm was generated.

- 23. (Currently amended) A method as recited in claim 22, wherein the [identifying means] array proximate each said <u>fill</u> port further contains port data relating to the type of fluid product to be distributed to the port.
- 24. (Currently amended) A method as recited in claim 22, wherein monitoring the source of each fluid product further comprises accessing a lookup table identifying the type of fluid product to be put into a particular <u>fill</u> port.
- 25. (Previously amended) A method as recited in claim 22, and further comprising the steps of determining the location of said vehicle to be serviced and the time of servicing, and reporting same for inclusion in said record.
- 26.(Currently amended) A method as recited in claim 22, and further comprising the steps of generating operator data identifying the operator responsible for servicing said vehicle, and transmitting said operator data to said remote receiver.

